

MODEL: REF10

PRODUCT ID: REF10D415





REF10 OWNER'S MANUAL

SHEET LIKE DANISH SQL AUDIOPHILE COMPONENTS

SWEET LIKE DANISH

MODEL: REF10





Model:	REF10D4	ENCLOSURE SUGGESTIONS	
Sensitivity:	89.4 dB		20 L / 0.71 cu.ft
Nominal Impedance:	Dual 4 Ω	SEALED	Qtc 0.3
DC Resistance (DC) Parallel:	1.6 Ω		
Voice Coil Dim:	3"		35 L / 1.23 cu.ft
Power Handling*:	600 Watts	PORTED COMPACT	P: 4" L: 16.9"
Peak Dynamic Power:	1200 Watts		FB: 36 Hz
XMAX one way (mm):	15		
VAS:	22.7 L		50 L / 1.76 cu.ft
FS:	28 Hz	PORTED	P: 4" L: 20.7"
QES:	0.26		FB: 28 Hz
QMS:	3,42		
QTS:	0.24		S: 20 L / 0.71 cu.ft
Magnet:	2 x 80 Oz	BP 4TH	P: 35 L / 1.23 cu.ft
Displacement:	4.1 L / 0.15 cu.ft		P: 4" L: 1"

^{*}It's essential that our speakers are given time to allow the suspension to soften up. Depening on use, this may take several weeks. While this process is undergoing, it is not recommended to apply full amplification power according to the speaker's specs. Once the moving parts have been broken in, the performance of your speaker will increase. Abuse of the the unit is **not** covered by warranty.

The warranty does not cover (1) Speakers that have been used for spl purpose in competitions, (2) Damage caused by amplifier clipping or distortion, (3) Exposure to water, oil, solvent & excessive temperatures +/-. (5) Cost of shipping to / from authorized service center.