



RAMPAGE SUBWOOFERS

MODEL: RAMPAGE1201

MODEL: RAMPAGE15D1


PRODUCT ID: RAM12D118


PRODUCT ID: RAM15D118


WWW.B2AUDIO.COM / WWW.FACEBOOK.COM/B2AUDIO




MODEL: RAMPAGE12 / RAMPAGE 15









Model:	RAMPAGE12D1	RAMPAGE15D1
Sensitivity:	87.8 dB	90.8 dB
Nominal Impedance:	Dual 0.8 Ω	Dual (),8 Ω
DC Resistance (DC):	1.8 Ω Series	1.8 Ω Series
Voice Coil Dim:	4"	4"
Power Handling*:	3000 watts	3000 watts
Peak Dynamic Power:	12000 watts	12000 watts
XMAX one way (mm):	40	40
VAS:	9.7 L	28 L
FS:	34.6 Hz	32.8 Hz
QES:	0.55	0.6
QMS:	7.21	8.63
QTS:	0.511	0.56
Magnet:	1100Oz	1100 Oz
Displacement:	10.2 L / .361 cu.ft	13.95 L / .49 cu.ft

ENCLOSURE SUGGESTIONS				
TYPE	SEALED	PORTED COMPACT	PORTED	
RAMPAGE12D1	30 L / 1.06 cu.ft	30 L / 1.06 cu.ft	60 L / 2.1 cu.ft	
	Qtc 0.481	P: 4" L: 18.3" / 46.6 cm	P.A. 15.5 sq.in L:14.5"	
		FB: 38 Hz	FB: 34 Hz	
	50.2 L / 1.77 cu.ft	56.3 L / 1.99 cu.ft	120 L / 4.2 cu.ft	
RAMPAGE15D1	Qtc 0.55	P.A. 18.6 sq.in L:14"	P.A. 31 sq.in L:14.7"	
		FB: 38 Hz	FB: 32 Hz	