AUDIOPHILE ACOUSTICS





The lunar deity 3 WAY SPEAKER SET

MODEL: MAN

PRODUCT ID: MANI6320

WWW.B2AUDIO.COM / WWW.FACEBOOK.COM/B2AUDIO / INSTAGRAM: B2\_AUDIO



# INTRODUCTION

Always striving for perfection has been the aim since we founded the company 2 decenniums ago. The Mani loudspeakers ushers in a new era of elitism. Natural materials such as wollen bamboo & premium silk enhances the strenght & the loudspeakers frequency response. The impact and coloring of the sound from the material is minimal, which is the cornerstone of any High Fidelity experience.

Implementation of our SAFT\* loudspeaker frame increases the soundwave with the least amount of resistance. The result is a loudspeaker that will have an optimized linearity throughout the audible range, a rather large side benefit is less amplified power needed to achieve that of other speakers comparable.

\*(Smooth Air Flow Tech)

Stay updated on B2 audio, follow us on social media & our website. www.b2audio.com - www.facebook.com/b2audio - www.instagram.com/b2\_audio www.youtube.com/b2audio - twitter: @b2\_audio











# **AUDIOPHILE ACOUSTICS**

IS THE DNA OF B2 AUDIO, ANY PRODUCT IS DEVELOPED BY ADDING THE UNIQUENESS AND THOUGHT OF EVOLUTION IN THE SPECIFIC APPLICATION OF THE PRODUCT'S DESIGN.

KEEP IN MIND THAT CONTINIOUS EXPOSURE TO SPL ABOVE 100 DB CAN SERIOUSLY DAMAGE YOUR HEARING. TODAY'S HIGH POWER AUTO SOUND SYSTEMS CAN EASILY PRODUCE SPL ABOVE 140 DB. ENJOY YOUR PASSION WITH SENSE AND RESPECT FOR THE ENVIRONMENT.

# TABLE OF CONTENTS

DESIGN FEATURES	3	NOTOPHILE ACOUSTICE
THIELE SMALL DATA	3	WILL SOLVE
FREQUENCY RESPONSE DIAGRAM	4-5	
CROSSOVER POINTS	6	STEFF LIKE DANISH

INSTALLATION

7

# Mani

# 3 Way Component Speaker System

Midwoofer: 6.5" Bamboo infused paper cone, strontium magnet structure 3" Bamboo infused paper cone, strontium magnet structure Midrange: 1.6" Silk dome tweeter, neodymium magnet structure Tweeter: 50 Hz ~ 25 KHz Frequency Response: Thiele Small data: Midwoofer Fs: 55 Hz Re: 3.6 Ω Qms: 2.68 Z nom: 4Ω Qes: 0.50 Voice coil: 1.2" Qts: 0.42 Rms: 2.45 Vas: 11.67 L Efficiency: 0.53% 6.39 TM Cms: 439 um/N BL: SPL: Mms: 16.4 g 89.6 dB Power handling: 100 w 0.264 mH Le: Thiele Small data: Midrange Fs: 159 Hz Re: 5Ω 5.54 Z nom: 5.2 Ω Qms: 1.43 1" Qes: Voice coil: 1.14 0.51 Qts: Rms: Vas: 0.5 L Efficiency: 0.142% Cms: 354 um/N BL: 3.2 TM

2.8 g

50 w

Tweeter data:

Power handling:

Mms:

Fs: 1250 Hz Qms: 0.76 2.43 Qes: 0.58 Qts: Vas: 0.001 L Cms: 5.7 um/N Mms: 2.8 g Power handling: 30 w

Re:  $3.9 \Omega$  Z nom:  $4 \Omega$  Voice coil: 1'' BL: 6 TM SPL: 84 dB

83.6 dB

0.21 mH

SPL:

Le:




# FREQUENCY DIAGRAM

Mani

Tweeter




Midrange



B<sup>2</sup>, andio

# FREQUENCY DIAGRAM

# Mani



# Combined frequency response




2 andio

# Mani



Woofer & Mid + 3 dB	Xover point:	1.25 KHz
Woofer & Mid + 0 dB	Xover point:	1.55 KHz
Mid + 3 dB & Tweeter + 3 dB	Xover point:	6.6 KHz
Mid + 3 dB & Tweeter + 0 dB	Xover point:	6.8 KHz
Mid + 0 dB & Tweeter + 3 dB	Xover point:	6.25 KHz
Mid + 0 dB & Tweeter + 0 dB	Xover point:	6.45 KHz

B<sup>2</sup> andio



## **INSTALLATION**

Prior to installation, ensure a proper location for the speaker system.

Due to the physical dimensions of the cabin, it is wise to test various points of placements if possible. If oem position is chosen, a good tip is to reinforce the mounting with a mdf ring and seal off leakage from that position. This will enhance mid bass response as well as optimizing overall performance. Do also try with slightly angling the midwoofer to "raise" the sound.

It is wise to keep both the midrange and tweeters in the same plane, this will make the sound appear more direct and it will cause less problems with an out of phase sensation.

The tweeters & midranges can preferably be mounted in a-pillars or placed close to the windscreen, mirroring of that and reflecting the sound towards the best audible position.

# AND TOPHILE ACOUSTICS

The lunar deity
3 WAY SPEAKER SET
LIKE DAMISH

### LIMITED WARRANTY INFORMATION

B2 audio offers a limited warranty under the following terms:

The product is to be free of defects in material & workmanship under normal use for a period of 1 year from the date of the original purchase, when installed by an authorized dealer. Items not installed by authorized dealers will be warrantied for 30 days from the original purchase. Original sales receips must be accompanied with all returns. The warranty applies to the original purchaser of the product & it being sold by authorized B2 audio dealers.

The warranty does not cover: 1. Damage caused by accident, abuse, misuse, improper operation, water / solvents & shipping.

- $\textbf{2. Product modification, neglect, failure to follow installation instructions \textbf{\& misrepresentation by the seller.}}\\$
- 3. Products used for competition purposes or are of such a charachter 4. Any product that has been opened.
- 5. Products that has had the serial number defaced, altered or removed.
- 6. The cost of shipping the product back for repair to an authorized repair centre & cost of return of non-defective items.